IAQ ALERT





SALIENT FEATURES

- ✓ High performance NDIR sensors and circuits, ensure accurate measurement and temperature compensation
- ✓ Fast and High Response Humi-Temp sensor for efficient operation.
- ✓ Easy Wall Mounting option.
- ✓ Inbuilt sensors for Temperature, Humidity & CO2
- ✓ Easy to carry, Plug & Play Instrument with power adapter (provided along with).
- ✓ Remote monitoring/controlling feature with RS485 Modbus communication.
- ✓ Bright LCD Backlight for better visibility

APPLICATIONS:

Offices, Smart Homes, Medical Lab, Patient Room, Green House, Warehouse, Hospitals, Food Industry, R&D Labs.

Specifications

Model Al-IAQ

Carbon Dioxide Range CO2: 0 to 5000 PPM

Temperature Range 0 to 50°C

Humidity Range 0 to 100% RH

CO2 Accuracy +/- 3% FS

Temp Accuracy ±0.5°C

Humidity Accuracy ±2% RH

Mounting Wall Mounting IP65 Enclosure with Integrated Sensor

Enclosure Wall mounting type ABS Plastic Enclosure with Wall Bracket

Power Supply 12 VDC Input with minimum of 2 amp current rating

Output RS 485 MODBUS Communication to connect SCADA/PLC/BMS

Display 128 x 64 Graphical large LCD Display with white backlight

Dimensions 120 (L) x 79(W) x 57 (D) mm

Make ACE Instruments

Instrukart Holdings

